

**MATTRESS FOR BEDDING, AND METHOD AND APPARATUS FOR
MANUFACTURING THE SAME**

5

Related Applications

This application is a continuation-in-part of PCT Application No. PCT/KR00/00160, filed March 2, 2000, designating the United States and, therefore, having the effect of a U.S. national application for patent under 35 U.S.C. § 363, which claims the benefit of earlier filing date of Korean Patent Application No. 1999/7131, filed March 4, 1999.

10

Background of the Invention

The present invention relates to a mattress for bedding, and more particularly to a mattress for bedding with threads installed therein and having air tubes containing a foamed body in order to maintain the cushion and the shape of the mattress and to improve its durability and to a method and an apparatus for manufacturing the mattress.

15

A conventional mattress for bedding is a type of mattress with a plurality of coil springs disposed therein and configured to maintain the cushion and shape of the mattress by means of elastic force and elastic restoring force by the plurality of coil springs.

20

However, such a mattress that has coil springs therein is subject to severe vibrations as an impact applied to a portion of the mattress is transferred to the surroundings of that portion, and a user cannot arbitrarily adjust a degree of cushion of the mattress in accordance with his body since the elastic force of the coil springs is predetermined upon their manufacture. Further, since the elastic force and elastic restoring force of the coil springs are lowered and noise is generated when the coil springs are used for a long period, it is difficult to maintain the cushion and shape of the mattress and in turn the life of the mattress is shortened.

25

In order to make up for the drawbacks in the coil springs, an air mattress using air was developed previously. That is, the air mattress is configured so that the inner portion of the air mattress is divided into a plurality of partitions by bonding both ends of a respective I-beam to upper and lower inner surfaces of the air mattress and air is injected into each partition. The air mattress is adapted to maintain its cushion and shape by air pressure that is injected into each partition and to arbitrarily set the degree of cushion in conformity to a user's body by adjusting the air pressure.

However, since the air mattress with I-beams installed therein has a plurality of partitions divided widthwise or lengthwise of the mattress, air is moved within the same partition when pressure is applied to a certain portion. Therefore, since a portion to which pressure is applied is recessed due to the depression of the air mattress and the other portions to which pressure is not applied relatively expand and convexly protrude, there is a drawback that the air mattress has on the whole a level of irregularity.

Moreover, if the expansion and contraction of the air mattress are repeated as it is repeatedly used, stress is concentrated on the inner surfaces of the mattress and on both ends of the I-beams attached thereto, and thus, the bonded portions of the I-beams are detached, thereby deteriorating the function of cushion and the shape maintenance, resulting in a useless mattress.

The applicant proposed an air mattress using threads in Korean Patent No. 226611 in consideration of the problems occurred in a mattress using coil springs and an air mattress using I-beams as described above.

That is, the air mattress is configured so that the inner top and bottom surfaces having gastight property (gas impermeability) and liquid-tight property (liquid impermeability) are densely connected by threads, for example, with the density of three or more strands per one square centimeter and air is injected into the air mattress. The air mattress is adapted to maintain its shape with the expansion of the air mattress by the length of the threads.

If the inner top and bottom surfaces are densely connected by a number of threads as described above, even though pressure is applied to a certain portion of the air mattress, only the portion to which the pressure is applied is recessed and the other

portions are prevented from further expanding by the length of the threads so that the other portions do not convexly protrude to maintain the shape of the air mattress and merely inner air pressure is slightly increased. Thus, the air mattress can be prevented from having on the whole a level of irregularity.

5 Further, since air pressure within the air mattress acts uniformly on the whole, stress affected on the individual thread is reduced and this stress is also dispersed due to the dense connections of the threads. Thus, there is no risk that connected portions of the threads are detached and so on, which results in the improvement of durability.

10 Although such an air mattress using threads described above is excellent, there is a further need for an air mattress that can maintain the cushion and shape of the mattress even when the air leakage occurs.

Summary of Certain Inventive Embodiments

15 The present invention is to solve the above problems in the prior art. Certain embodiments provide a mattress for bedding and a method and an apparatus for manufacturing the mattress, wherein vibrations due to impact can be reduced, the degree of cushion can be arbitrarily adjusted by a user in conformity to his body condition, and the life of the mattress can be extended by means of the improvement in the function of cushion and shape maintenance.

20 Certain embodiments provide a mattress for bedding having an air mattress in which time required for the injection of air can be shortened.

25 Certain embodiments provide a mattress for bedding and a method and an apparatus for manufacturing the mattress, wherein the mattress can be prevented from having a level of irregularity on the whole and the occurrence of failure due to stress concentration can be reduced.

Certain embodiments provide a mattress for bedding and a method and an apparatus for manufacturing the mattress, wherein the cushion and the shape of the mattress can be basically maintained even in the occurrence of an air leakage.

A mattress according to one aspect of the present invention comprises: a

mattress skin defining an enclosed space, the mattress skin comprises first and second walls, wherein the walls are oppositely configured to each other; a plurality of strings interconnecting the walls within the enclosed space, each of the string having two ends, wherein one end connects with the first wall, and wherein the other end connects with the second wall; and a resilient material located within the enclosed space, wherein at least part of the strings are embedded in the resilient material while interconnecting the walls.

In the mattress, the first and second walls are arranged substantially parallel to each other. The mattress skin defines the enclosed space substantially air-tight or liquid-tight. The enclosed space is filled with gas or liquid. The strings interconnecting the walls are substantially perpendicular to the walls connected therewith. The strings are made of a substantially non-elastic material. A tensile strength of the string is 120 daN/cm or more. The strings are of substantially same in length. The strings interconnecting the walls through the resilient material are substantially straight. A string density is at least one string per one square centimeter of the inner surfaces. A string density may be at least three strings per one square centimeter of the inner surfaces. The resilient material substantially may fill up the enclosed space. The resilient material partly may fill the enclosed space. The resilient material comprises a porous body allowing gas or liquid to pass therethrough. The resilient material comprise a foam material. The resilient material is made of a resin selected from the group consisting of polyurethane, polyethylene, polypropylene, latex, polyvinyl chloride. The mattress further comprises an extra skin and a cushion member, wherein the extra skin encloses the mattress skin and the cushion member.

A method of manufacturing a mattress according to another aspect of the present invention comprises: providing first and second walls; interconnecting the walls with a plurality of strings, each string having two ends, wherein one end connects with the first wall, wherein the other end connects with the second wall, and wherein the walls are oppositely configured to each other; separating the interconnected opposite walls from each other with a distance so as to define a space therebetween; and providing a resilient material embedding at least part of the strings in the space while maintaining the inner

surfaces separated.

5 The method further comprises coupling at least one wall with the first and second walls so as to enclose the space. The method further comprises filling gas or liquid into the enclosed space of the mattress. The providing resilient material comprises embedding at least part of the strings in the resilient material with the connections of the strings with the wall substantially intact. The providing resilient material comprises generating foam. The generation of foam comprises injecting a foam generating composition into the space and initiating foaming. The initiation of foaming comprises subjecting the composition injected in the space to an elevated temperature. The initiation of foaming comprises placing the intermediate for manufacturing a mattress in an oven at an elevated temperature. The distance between the wall are maintained substantially unchanged, during the providing resilient material.

15 Still another aspect of the present invention provides an apparatus for manufacturing a mattress for bedding, which has a top wall, a bottom wall and a lateral wall connecting the top and bottom wall. The apparatus comprises: a mattress mold including a bottom panel having a size corresponding to the bottom wall of said mattress, a side rim capable of being connected to said bottom panel and having a height corresponding to the lateral wall of said mattress, and a top panel to be connected to said side rim and having the size corresponding to a top surface of said mattress; a foam material supplying device for supplying a foam material having a tube extending within said mattress mold; and wherein margins of said bottom panel, side rim and top panel are provided with inclined surfaces abutted against each other when said panels and rim are assembled into a closed arrangement.

25 Brief Description of the Drawings

The above and other objects, advantages and features of the invention will be apparent from a preferred embodiment of the invention described with reference to the accompanying drawings briefly described below.

30 Figure 1 is a partially cut-away perspective view of a mattress according to an embodiment of the present invention;

Figure 2 is an enlarged sectional view showing the inner structure of the mattress according to the embodiment shown in Figure 1;

Figure 3 is a sectional view showing an embodiment of the mattress according to the present invention, which may or may not incorporate the embodiment shown in Figure 1;

Figure 4 is a perspective view showing an embodiment of an apparatus for manufacturing a mattress according to the present invention; and

Figures 5a and 5b are views for illustrating a method for manufacturing a mattress carried out by the apparatus for manufacturing the mattress according to the present invention.

Detailed Description of Certain Inventive Embodiments

Hereinafter, various features and aspects of the present invention will be explained in detail with reference to the embodiments illustrated in the accompanying drawings.

Figure 1 is a partially cut-away perspective view showing an air mattress according to the present invention, Figure 2 is an enlarged sectional view of a portion of the mattress according to the present invention, and Figure 3 shows a mattress main body (assembly) on which an air mattress is mounted. A mattress main body 10 of the invention consists of an air mattress 20, first and second cushion members 70 and 80, and a cover 30 for wrapping the members (refer to Figure 3).

The air mattress 20 includes a pair of top and bottom sheets 21 and 22 disposed opposite to each other on top and bottom sides, and the sizes of the top and bottom sheets 21 and 22 are set in accordance with the size of the mattress to be manufactured.

The top and bottom sheets 21 and 22 are connected by threads 23 so that the spacing between the top and bottom sheets 21 and 22 is maintained constantly when a foamed body 28 to be described later is inserted therein. That is, respective inner skins 24 and 25 are bonded to the top and bottom sheets by an adhesive. Adhesive layers 26 and 27 are formed between the top and bottom sheets 21 and 22 and the respective inner

skins 24 and 25. The thread 23 penetrates the inner skin 24 on the side of the top sheet 21 and is fixed to the adhesive layer 26, and subsequently penetrates back the inner skin 24 on the side of the top sheet 21. Then, it penetrates the inner skin 25 on the side of the bottom sheet 22 and is fixed to the adhesive layer 27, and subsequently penetrates back the inner skin 25 on the side of the bottom sheet 22.

By repeating the above fixation process with the threads 23, the top and bottom sheets 21, 22 are densely and vertically connected with the threads 23. At this time, the lengths of the threads 23 connecting the top and bottom sheets 21 and 22 are made uniform so that the spacing between the top and bottom sheets 21 and 22 can be kept constant. In order to maintain the durability and the shape of the mattress, the sheets are connected, preferably, by at least one strand of thread 23 per one square centimeter, and most preferably, by three or more strands of threads 23 per one square centimeter.

A foamed body 28 is provided between the top and bottom sheets 21 and 22, more accurately, between the respective inner skins 24 and 25. The foamed body 28 is formed by filling a space between the top and bottom sheets 21 and 22 with a foam material and by foaming this material, which will be described later. With the foamed body 28, the top and bottom sheets 21 and 22 are configured to have a uniform spacing between them so that the mattress can maintain the shape as well as a desired cushion.

As the foam material for forming the foamed body 28, it includes a mixture of a foam resin such as polyurethane, polyethylene, polypropylene, latex, PVC, etc., with a foaming agent which is compatible with the foam resin and typically vaporizes above a certain temperature. After foaming of the foam material, the foaming agent vaporizes and forms fine cells (bubbles) 28a in the foamed body 28, so that the cushion of the foamed body 28 itself can be set in accordance with the amount of the foam material. It is preferred that the cells of the foamed body 28 are open cells.

Each thread 23 densely connected between the top and bottom sheets 21 and 22 is embedded in the foamed body 28 and spaced apart from each other by the foamed body 28. Numerous fine cells 28a are formed within the foamed body 28 and communicate with the outside of the foamed body 28 so that air can enter and leave the cells.

The top and bottom sheets 21 and 22 have wings (flaps) 21a and 22a extending outwardly from the regions in which the sheets are connected to each other by threads. A side sheet 29 is connected to the wings (flaps) 21a and 22a. As can be seen in Figure 1, the side sheet 29 is attached around the entire margins of the top and bottom sheets 21 and 22.

The top and bottom sheets 21 and 22 and the side sheet 29 have impermeability against air (airtight property) and should be made of a material that can resist the inner air pressure. As the material for the sheets 21, 22 and 29, it includes a material having airtight property such as PVC, PU, rubber, etc. As the inner skin 23 and 24, woven fabric is used. Preferably, fabric woven from polyester or nylon 66 fiber is used. It is preferred that the thread 23 has tensile strength that can resist the inner air pressure. Preferably, the tensile strength is 120 daN/cm or more. It is preferred that the thread is made of a material consisting of polyester or nylon 66.

At least one air valve 30 is provided on a side of the air mattress 20.

As shown in figure 3, the mattress main body 10 according to the present invention may be configured to have several parts. Where bedding is configured to have several parts, it is preferred that the air mattress 20 according to the present invention is arranged only in the central portion of the bedding to which pressure is applied most greatly and that the cushion members 70 and 80 are disposed at front and rear portions, i.e., head and foot portions of the bedding. Although a cushion member made of any known material may be used, a cushion member made of palm fiber (cushion member made by dipping and fixing palm fiber into liquid latex) or other cushion members made of PE may also be used. Alternatively, the bedding may consist of only the air mattress 20.

Referring to Fig. 4, an apparatus for manufacturing the air mattress according to the present invention will be described. The apparatus for manufacturing the air mattress comprises a mattress mold 40 and a device for supplying a foam material to form the foamed body 28 by injecting the foam material into the mold 40.

The mold 40 comprises a bottom panel 41, two side panels 42 and 43, front and rear panels 44 and 45, and a top panel 46 having respective sizes that correspond to the

bottom surface of the bottom sheet 22, the opposite side surfaces, the front and rear surfaces, and the top surface of the air mattress 20, respectively.

5 The opposite side panels 42 and 43 and front and rear panels 44 and 45 are connected to the bottom panel 41 in a manner that each of the panels 42, 43, 44, or 45 is able to be folded onto the bottom panel 41 at approximately 90 degrees. The top panel 46 is foldably connected to one of the side panels 43 at about 90 degrees. As shown in Figs. 5a and 5b, inclined surfaces 41a to 46a that are preferably inclined at about 45 degrees are also formed at the margins of the bottom panel 41, side panels 42 and 43, front and rear panels 44 and 45, and top panel 46. The inclined surfaces abut against each other at a position where all the panels are closed. In the closed position, locking members 47 are mounted so as to fasten the front and rear panels 44 and 45 and side panel 42 to the top panel 46.

15 The foam material supplying device for injecting a foam material into the mattress mold 40 comprises a container 50 for storing the foam substance (or foam material) and a supplying line 51 for providing paths to feed the foam material into the mattress mold 40.

20 The foam material is obtained by mixing a foam liquid for forming the foamed body 28 and a foaming agent for forming fine cells 28a in the foamed body 28, at a predetermined ratio. Polyurethane, polyethylene, polypropylene, latex, PVC, etc. may be used as the foam liquid, and the polyurethane is more ideal. Any foaming agent may be used if it is supposed to evaporate, but the foaming agent should be compatible with the foam liquid. Any kinds of foam liquid and foaming agent that are known to a person skilled in the art may be used.

25 The container 50 includes a first storage container 50a for storing the foam liquid and a second storage container 50b for storing the foaming agent.

30 The supplying line 51 comprises feeding lines 52 that are separately connected to each of the first and second storing containers 50a and 50b, a main line 53 at which the feeding lines 52 are combined so that the foam liquid and foaming agent can be mixed with each other, and a plurality of branched injection lines 54 that are derived from the main line 53 and divided into several lines connected to the side panel of the

mattress mold 40 so that the foam material can be uniformly and rapidly injected into the mold 40.

The injection lines 54 are constructed to reciprocally move in their linear direction as designated by the arrows shown in Fig. 4 with a conventional conveying device (not shown). Preferably, the injection lines 54 are constructed to inject the foam material into the mold 40 via through-holes 42b that are formed on the side panel 42 as they come out from the inner part of the inside of the mold 40 in a direction designated by an arrow Y. Alternatively, the mattress mold 40, instead of the injection lines 54, may be linearly displaced in a direction designated by the arrow X.

The supplying line 51 further includes a pump 55 for forcedly feeding the foam material into the main line 53 and a flow control valve 56 for controlling the amount of foam material to be injected.

Referring now to Figs. 4, 5a and 5b, the operation of the apparatus for manufacturing the mattress as constructed above will be described together with a method for manufacturing the mattress. Firstly, as shown in Fig. 4, the top and bottom sheets 21 and 22 of the size corresponding to that of the mattress are disposed to face each other. The threads 23 are densely connected to all portions except for the wings 21a and 22a of the margins of the top and bottom sheets 21 and 22 with the top and bottom sheets 21 and 22 maintained at a constant spacing between them. It is preferred that three strands of threads 23 per 1 square centimeter of the top and bottom sheets 21 and 22 are connected to the sheets.

Then, the top and bottom sheets 21 and 22 that are connected to each other with the threads 23 are inserted into the mattress mold 40. As shown in Figs. 5a and 5b, the margins of the top and bottom sheets 21 and 22 are inserted between two of the inclined surfaces 41a to 46a of the bottom panel 41, side panels 42 and 43, front and rear panels 44 and 45 and top panel 46. Thereafter, when the side panels 42 and 43, front and rear panels 44 and 45 and top panel 46 are folded into the closed position, the respective wing 21a or 22a of the margins of the top and bottom sheets 21 and 22 is pressed and fixed between the respective inclined surfaces 41a to 46a. The top and bottom sheets 21

and 22 are tightly stretched in a horizontal direction within the mattress mold 40 and at the same time, are maintained in a vertical direction at a constant spacing between them.

Next, the side panels 42 and 43, front and rear panels 44 and 45 and top panel 46 are fixed by the locking members 47. Then, the injection lines 54 of the supplying line 51 are moved in the direction designated by arrow X and inserted into the mattress mold 40 via the through holes 42b. Thereafter, the pump 55 is actuated and the foam liquid and foaming agent that are stored in the first and second storing containers 50a and 50b, respectively, are forcedly fed. The foam liquid and foaming agent are mixed in the main line 53 during their feeding. The mixed liquid is injected into the mattress mold 40 through the plurality of branched injection lines 54, and a first foaming of the mixed liquid is performed within the mold. At this time, the amount of foam material for injection is controlled by the flow control valve 56. Uniform injection can be achieved by moving the injection lines 54 from the inner part of the inside of the mattress mold 40 in the direction designated by the arrow Y while injecting the mixed liquid into the mold.

The first foaming of the foam material is performed at room temperature. After the first foaming is completed, a second foaming of the foam material is carried out at a temperature higher than room temperature. The second foaming may be carried out by, for example, putting the mattress mold 40 into an oven (not shown) and keeping a high temperature of about 80 °C for 20 minutes. When the second foaming is performed, the foam liquid is fully foamed and turned into the foamed body 28 having the fine cells 28a. Resulting foamed body 28 is formed between the top and bottom sheets 21 and 22 with the threads 23 being embedded therein.

Finally, the air mattress 20 of the present invention is produced by removing the mattress 20 from the mattress mold 40, attaching an airtight and liquid-tight side sheet 30 to the mattress 20 for the purpose of sealing, and pumping air into the air mattress 20 through valves 31.

Resulting air mattress 20 expands with the pressure of air as air is injected into the mattress 20 through the valves 31. Expansion of the mattress is controlled by the threads 23 that connect the top and bottom sheets 21 and 22, and thus the shape of the

air mattress 20 remains constant.

The air mattress 20 becomes gradually harder if the inner air pressure continuously increases in a state that the mattress 20 does not expand any more. Accordingly, cushion of the air mattress 20 can be arbitrarily set by adjusting the air pressure within the air mattress 20 as mentioned above.

Furthermore, since the top and bottom sheets 21 and 22 of the air mattress 20 are constructed to be connected to each other by means of the dense threads 23, stress of the mattress due to a pressure or an impact is distributed and thus its durability is improved. The air tube 20 is also prevented from expanding beyond a certain limit. Therefore, even though a portion of the mattress 20 is pressed, merely the pressed portion is recessed and the other portion that is not pressed does not protrude and remains unchanged. Thus, the mattress 20 is prevented from having on the whole a level of irregularity and vibrations are not transmitted through the mattress.

On the other hand, even though air leaks out through the air valves 31, a basic shape of the mattress 20 is maintained as the foamed body 28 is provided within the mattress 20. Minimum cushion of the mattress 20 may also be maintained due to the inherent resiliency of the foamed body 28. Further, since the plurality of the threads 23 are separately embedded in the foamed body 28 and are spaced apart from each other, tangling of the thread 23 due to its slackness during contraction of the air mattress 20 is prevented.

Although the mattress 20 has been described in the form of an air mattress in the embodiments, the present invention is not limited to the above, and liquid such as water may be contained within the mattress 20.

As mentioned above, since the mattress for bedding according to the present invention is constructed such that its inner portions are connected with each other by the dense threads and the foamed body is provided within the mattress while the air is injected/inserted therein, the vibrations due to impact can be reduced and the cushion can be arbitrarily adjusted in accordance with a user's body. Upon use of the mattress, the mattress is prevented from having on the whole a level of irregularity, and the occurrence of failure due to stress concentration is reduced and thus its life can be

extended. Further, the basic cushion and shape of the mattress can be maintained even though air may leak out from the air mattress. Furthermore, since the foamed body is provided within the air mattress, the amount of injected air can be reduced and thus the time for air injection can be shortened.

5 Although the present invention has been described with reference to the above preferred embodiments, it should be understood that any changes or modifications may be made without departing from the scope and spirit of the invention and that they will be within the scope of the present invention which is defined in the claims attached hereto.

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213